

speco technologies®

Intensifier™ 2 Series Weatherproof Dome Cameras



*Includes
EZ Mount Plate*



- HTINTD8** (2.8-12mm lens)
- HTINTD9** (5-50mm lens)
- HTINTD10** (9-22mm lens)

Features	
<i>See In The Dark Without IR LEDs</i>	
<ul style="list-style-type: none"> • Weatherproof operation, IP-67 • Tamper resistant • Amplify existing light with no distance limitations • No problems caused by objects that reflect or absorb IR light sources • 580 lines of resolution • Min. illumination 0.002 lux (Intensifier™ @ 256x) • Featuring HLC for enhanced backlight operation • Digital Image Stabilization 	<ul style="list-style-type: none"> • Advanced noise reduction circuitry eliminates blur • Relay outputs for built-in video motion detection • Dual voltage 12V DC & 24V AC operation • Full OSD operation • External controls for zoom and focus • SLC - Speco Light Compensation • S/N Ratio more than 52dB (weight on) • EZ mount system simplifies installation • Wall & ceiling mountable

Specifications

Image Pick-Up Device	1/3" Sony Super-HAD™ CCD - 410K
Resolution	580 TV lines
Minimum Illumination	0.002 lux - (Intensifier™ @ 256x)
S/N Ratio	More than 52dB (weight on)
White Balance	ATW/AWC/MANUAL (1800K - 10,500K)
Video Output	Composite video 1.0 Vp-p into 75 Ohm + test connection
Electronic Shutter	Auto/Manual (1/60 - 1/120,000 seconds)
On Screen Display (OSD)	Built-in - controlled by internal buttons
Motion Detection	8 zones - relay outputs
HLC/SLC (Speco Light Compensation)	Advanced backlighting controls
Auto Gain	Low, middle, High, Off, Selectable
S-DNR Video Noise Reduction	Low, middle, High, Off, Selectable
Day & Night (Color)	On / Auto Selectable
Sharpness	On / Off (Level Adjustable)
Privacy	On / Off (8 Programmable Zones)
Power Supply	24 Volts AC, 12 Volts DC - Dual Voltage
Power Consumption	250mA
Lens	DC Auto Iris Varifocal Lens (2.8-12mm, 5-50mm or 9-22mm)
Total Pixels	811(H) x 508(V)
Effective Pixels	768(H) x 494(V)
Scanning Frequency	15.734kHz(H) / 59.94Hz(V)
Scanning System	2:1 Interlace
Synchronization	Internal / Line lock in 24V AC
Operating Temperature	-20°F to 120°F - RH 95% Max.
Storage Temperature	-40°F to 140°F - RH 95% Max.
TV System	NTSC
Dimensions	5.5" W x 4.4" H x 5.5" D
Weight	3 lbs.

<i>Optional Accessories:</i>	
CVCTPEXT	Junction Box used for connections and/or conduit applications
7246WMT	Weatherproof wall mount for use with many Speco Dome Cameras

Specifications subject to change